

NO.	Series	Size	SL/XL	Sidewall Type	Rim	PR	LI/SS	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max.Air Pressure (KPa)	Max.Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	50"	215/50R17	XL	BSW	7.0	-	95V	690	1521	340	50	8.7	226	648
2		225/50R17	SL	BSW	7.0	-	94V	670	1477	350	51	8.7	233	658
3	55"	205/55R16	SL	BSW	6.5	-	91V	615	1356	350	51	8.7	214	632
4		215/55R17	XL	BSW	7.0	-	98V	750	1653	340	50	8.7	226	668
5		215/55R17	SL	BSW	7.0	-	94V	670	1477	350	51	8.7	226	668
6		235/55R18	SL	BSW	7.5	-	100V	800	1764	350	51	8.7	245	715
7	60"	175/60R13	SL	BSW	5.0	-	77H	412	908	350	51	8.7	177	540
8		185/60R14	SL	BSW	5.5	-	82H	475	1047	350	51	8.7	189	578
9		185/60R15	SL	BSW	5.5	-	84H	500	1102	350	51	8.7	189	603
10		195/60R14	SL	BSW	6.0	-	86H	530	1168	350	51	8.7	201	590
11		195/60R15	SL	BSW	6.0	-	88H	560	1235	350	51	8.7	201	615
12		205/60R16	SL	BSW	6.0	-	92V	630	1389	350	51	8.7	209	652
13		215/60R16	SL	BSW	6.5	-	95V	690	1521	350	51	8.7	221	664
14		225/60R16	SL	BSW	6.5	-	98H	750	1653	350	51	8.7	228	676
15	65"	155/65R13	SL	BSW	4.5	-	73T	365	805	350	51	8.2	157	532
16		165/65R13	SL	BSW	5.0	-	77T	412	908	350	51	8.2	170	544
17		175/65R14	SL	BSW	5.0	-	82H	475	1047	350	51	8.7	177	584
18		185/65R14	SL	BSW	5.5	-	86H	530	1168	350	51	8.7	189	596
19		195/65R15	SL	BSW	6.0	-	91H	615	1356	350	51	8.7	201	635
20		205/65R15	XL	BSW	6.0	-	99T	775	1709	340	50	8.7	209	647
21		205/65R16	SL	BSW	6.0	-	95V	690	1521	350	51	8.7	209	672
22		215/65R16	SL	BSW	6.5	-	98H	750	1653	350	51	8.7	221	686
23		225/65R17	SL	BSW	6.5	-	102H	850	1874	350	51	8.7	228	724
24	70"	165/70R13	SL	BSW	5.0	-	79T	437	963	350	51	8.2	170	562
25		175/70R13	SL	BSW	5.0	-	82T	475	1047	350	51	8.7	177	576
26		175/70R14	SL	BSW	5.0	-	84T	500	1102	350	51	8.7	177	602
27		185/70R14	SL	BSW	5.5	-	88T	560	1235	350	51	8.7	189	616
28		195/70R14	SL	BSW	6.0	-	91T	615	1356	350	51	8.7	201	630
29		205/70R15	SL	BSW	6.0	-	96T	710	1565	350	51	8.7	209	669
30		215/70R15	SL	BSW	6.5	-	98T	750	1653	350	51	8.7	221	683